

Specifications for Memorials

All new memorials and where practicable re-fixed memorials are to be fixed in the cemetery in accordance with the Code of Working Practice from the National Association of Memorial Masons.

Materials for Memorials

Permanent memorials must be made of best quarried materials. Limited use of etched and enameled ornamentation will be accepted subject to the approval of the Cemetery Manager.

All dowels shall be in accordance with the specification detailed in the National Association of Memorial Masons Code of Working Practice (NAMM). Portland, Caen, Bath, soft York stone or other free stone must not be used.

A base forming an integral part of the design of a headstone will not project more than 2 inches (50mm) beyond the headstone to the rear and sides and provided it is fixed onto the precast concrete raft.

Full Burial Sections

Memorials in these sections will be:

- No more than 48" (1200mm) in height including the base
- No more than 42" (1100mm) in width including the base
- Headstones to be no more than 6" (150mm) thick
- Base to be no more than 12" (300mm) in depth including the headstone

Book-sets must be a maximum of 15" (380mm) in height (overall)

Memorial Inscriptions

All inscriptions will be either bronze, lead, raised, or incised and painted, or carved on relief, or of gilded lettering.

Every memorial will have the grave number and name of the Memorial Mason inscribed upon it, in lettering not more than ½ inch (12mm) in height and 6" (150mm) in length - in the case of headstones, this will be on the base.

Cremated Remains Sections

Memorials in these sections will be:

- Cremated remains lawn memorial shall be:
- No more than 36" (900mm) in height including the base
- No more than 27" (685mm) wide
- Headstones to be no more than 6" (150mm) thick
- Base to be no more than 12" (300mm) in depth including the headstone

Flat Plaque Memorials to be installed on top of the memorial base the plaque shall be:

No more than 17" (432mm) in length and 27" (686mm) in width (landscape) and 2" thick (50mm)